



Product Information

CT 234 Medium Grade Brown Flatback Tape

Description:

Considered as the "Industry Standard." Aggressive, pressure-sensitive brown flatback paper tape that has been specifically designed to offer a strong secure seal on a variety of substrates. This product is moisture resistant and performs well under a wide range of temperature and humidity conditions. Has an excellent balance between machine and cross direction tensile and tear strength in order to reduce failures in the field, specifically in medium duty splicing, tabbing, and core starting applications. Product is not repulpable.

Application:

- Carton sealing, packaging, silk screening, and picture framing.
- Picture framing, beaming/leasing, and silk screening.

Government Compliance: Approved as packaging tape by both U.S. Postal Service and U.P.S. (United Parcel Service); PPP-T-42C, Type II; C.I.D. A-A-883B, Type II

Technical Data	
<i>Adhesive</i>	Solvent Cast Natural/Synthetic Rubber
<i>Substrate</i>	Kraft Flatback
<i>Thickness (mils)</i>	7.5 (0.19 mm)
<i>Adhesion to Steel (oz/in of width)</i>	68 (18.6 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	40 (175 N/25mm)
<i>Elongation (% at Break)</i>	7
<i>Service Temperature</i>	32°F to 200°F (0°C to 93°C)
<i>Application Temperature</i>	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.