



Product Information

CT #602

Contractor Grade Waterproof Polycoated Duct Tape

602 is a contractor grade and waterproof polycoated cloth duct tape with a natural rubber adhesive (silver and other colors available).

Meets Specs: UL 723, Flame Spread Index-5, Smoke Development Index-25.

Application:

- Demanding uses with HVAC flex ducts, sheet metal, exhaust vents, and pre-formed insulation
- Industrial packaging, splicing, and securing
- Excellent stretch, conformability, and easy unwind

TECHNICAL DATA

Adhesive	Natural Rubber
Substrate	Waterproof Polycoated Cloth
Thickness	11 Mils (0.28 mm)
Adhesion to Steel	62 oz/in (6.79 N/10mm)
Tensile Strength	27 lbs/in (47.3 N/10mm)
Elongation (% at Break)	10
Service Temp. Min	50°F (10°C)
Service Temp. Max	200°F (93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.