



Product Information

CT #608

Laminated FSK

608 is a laminated foil/scrim/kraft (FSK) with extremely high tack and an aggressive rubber-based adhesive with a removable liner.

Meets Specs: UL 723, Flame Spread Index-10, Smoke Development Index-25; ASTM E-84.

Application:

- Engineered to seam and seal fiberglass duct board and duct wrap to maintain vapor barrier integrity
- Adheres tightly when smoothed down

TECHNICAL DATA

Adhesive	Aggressive Rubber-Based
Substrate	Laminated FSK
Thickness	6.5 Mils (0.165 mm)
Adhesion to Steel	90 oz/in (9.9 N/cm)
Tensile Strength	30 lbs/in (53 N/cm)
Elongation (% at Break)	1
Application Temp. Min	-25°F (-32°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.