



Product Information

CT #657

Premium Printed Polycoated Cloth Duct Tape

657 is a premium grade, printed polycoated cloth duct tape with a UL 181B-FX adhesive system.

Meets Specs: UL 723; UL 181B-FX, Flame Spread Index-15, Smoke Development Index-30.

Application:

- HVAC flex duct applications, installing air ducts, air connectors
- Making connections and splices
- Resists flame spread, smoke generation, mold growth, humidity, and high temperatures

TECHNICAL DATA

Adhesive	UL 181B-FX Adhesive System
-----------------	----------------------------

Substrate	Waterproof Polycoated Cloth
------------------	-----------------------------

Thickness	14 Mils (0.36 mm)
------------------	-------------------

Adhesion to Steel	70 oz/in (7.66 N/10mm)
--------------------------	------------------------

Tensile Strength	27 lbs/in (47.3 N/10mm)
-------------------------	-------------------------

Elongation (% at Break)	10
-----------------------------------	----

Service Temp. Min	50°F (10°C)
--------------------------	-------------

Service Temp. Max	212°F (100°C)
--------------------------	---------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.