



Product Information

CT #953

Dead Soft Aluminum Foil Tape

953 is a 3 mil, dead soft aluminum foil tape with an aggressive acrylic adhesive with no release liner. It is also available with a paper release liner (#954).

Meets Specs: L-T-80B, MIL-T-23397B;
AMDT 2 TYPE II.

Application:

- Designed for use on variety of flat, irregular, or curved surfaces for vapor barrier protection, waterproof sealing, heat reflection/dissipation, masking for pain stripping, and electroplating
- Has high adhesion to backing
- May be applied at low temperatures
- Has good high/low temperature resistance

TECHNICAL DATA

| | |
|------------------------------------|------------------------------------|
| Adhesive | Acrylic |
| Substrate | Dead Soft Aluminum Foil |
| Thickness | 4.5 Mils (0.114 mm) |
| Adhesion to Steel | 50 oz/in |
| Tensile Strength | 28 lbs/in |
| Elongation (% at Break) | 5 |
| Temperature Range | -30°F to 325°F (-34°C to 163°C) |

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.