



Product Information

CT #770

General Purpose Clear Polyethylene Film Tape

770 is a clear polyethylene film tape with a rubber adhesive, used as a general purpose tape for LDPE splicing and patching.

Application:

- General purpose tape for LDPE splicing and patching

TECHNICAL DATA

Adhesive	Rubber
Substrate	Clear Polyethylene Film
Thickness	8 Mils (0.203 mm)
Adhesion to Steel	25 oz/in (2.74 N/cm)
Tensile Strength	15 lbs/in (26.27 N/cm)
Elongation (% at Break)	450%
Operating Temperature	50°F to 190°F (10°C to 88°C)
Application Temperature	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.