



Product Information

CT #737

Premium Performance OPP Film Tape

737 is a heavy duty grade, 1.6 mil, low elongation cast OPP film with an aggressive natural rubber adhesive.

Application:

- Used in both manual and automated applications where a premium performance tape is needed
- Performs well in sub-zero temperatures, freezer environments, and unheated warehouses

TECHNICAL DATA

Adhesive	Natural Rubber
-----------------	----------------

Substrate	OPP Film
------------------	----------

Thickness	2.3 Mils (0.058 mm)
------------------	------------------------

Adhesion to Steel	21 oz/in (23 N/100mm)
--------------------------	--------------------------

Tensile Strength	29 lbs/in (508 N/100mm)
-------------------------	----------------------------

Elongation (% at Break)	175
-----------------------------------	-----

Operating Temperature	-30°F to 200°F (-35°C to 93°C)
------------------------------	-----------------------------------

Application Temperature	32°F to 120°F (0°C to 49°C)
--------------------------------	--------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.