



## Product Information

### CT #714

### High Performance Grade BOPP Film

714 is a high performance grade, 50  $\mu\text{m}$  cast biaxially-oriented polypropylene film with a synthetic rubber/resin hot melt adhesive.

Meets Specs: CID-A-A-1684C; ASTM-D1974; ASTM D-5486M; AFTS-100-93.

#### Application:

- Extremely tough tape for the most demanding manual and automated packaging applications
- Excellent quick grab and holding power for heavy bulky cartons exposed to high stress handling

#### TECHNICAL DATA

<b>Adhesive</b>	Synthetic Rubber/Resin Hot Melt
<b>Substrate</b>	50 $\mu\text{m}$ Cast BOPP Film
<b>Thickness</b>	3 Mils (0.08 mm)
<b>Adhesion to Steel</b>	58 oz/in (6.35 N/10mm)
<b>Tensile Strength</b>	42 lbs/in (73.6 N/10mm)
<b>Elongation</b> (% at Break)	150
<b>Service Temperature</b>	-20°F to 150°F (-29°C to 66°C)
<b>Application Temperature</b>	35°F to 110°F (2°C to 43°C)
<b>Holding Power to Fiberboard</b>	30,000+ minutes

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.