



## Product Information

### CT #739

### High Performance Polyester Film Tape

739 is a high performance grade film tape with a 2 mil polyester film backing and a natural rubber adhesive.

Meets Specs: UFC Rule 41; DOT Spec 12B for hazardous shipments

#### Application:

- Very rigorous tape for manual and automated carton sealing applications

#### TECHNICAL DATA

<b>Adhesive</b>	Natural Rubber
-----------------	----------------

<b>Substrate</b>	2 Mil Polyester Film
------------------	----------------------

<b>Thickness</b>	2.9 Mils (0.074 mm)
------------------	------------------------

<b>Adhesion to Steel</b>	40 oz/in
--------------------------	----------

<b>Tensile Strength</b>	50 lbs/in
-------------------------	-----------

<b>Elongation</b> (% at Break)	110
-----------------------------------	-----

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.